

SÉRIE A

A60


A80

A90

A100



MODÈLE	A60	A80	A90	A100
LARGEUR DE COUPE (mm)	600	800	900	1060
EXCAVATRICE RECOMMANDÉE (tonnes)	1,5-2,5	2-3	2.5-4	3.5-5
POIDS (Kg)	105	115	145	180
PRESSIION D'HUILE (bar)	200	200	200	200
DÉBIT D'HUILE (l/min)	20-50	20-50	30-80	30-80
NOMBRE DE COUTEAUX	24	32	36	48
NOMBRE DE CLUBES	12	16	12	16
DIAMÈTRE DE COUPE MAXIMUM (mm)	20	20	35	35
DIMENSION A (mm)	680	680	680	680
DIMENSION B (mm)	830	1010	1110	1275
DIMENSION C (mm)	440	440	440	440
POIDS DE LA SELLE BASCULANTE (Kg)	27	27	27	27
POIDS DE L'ACCESSOIRE DE L'EXCAVATRICE (min-max Kg)	10-15	10-15	10-15	10-15



SÉRIE AR

(Réversible sans
rouleau de support)

A60R / A80R

A90R / A100R



MODÈLE	A60R	A80R	A90R	A100R
LARGEUR DE COUPE (mm)	600	800	900	1060
EXCAVATRICE RECOMMANDÉE (tonne) 1,5-2,5	2-3	2.5-4	3.5-5	
POIDS (Kg)	105	115	145	180
PRESSIION D'HUILE (bar)	200	200	200	200
DÉBIT D'HUILE (l/min)	20-50	20-50	30-80	30-80
NOMBRE DE COUTEAUX	24	32	36	48
NOMBRE DE CLUBES	12	16	12	16
DIAMÈTRE DE COUPE MAXIMUM (mm)	20	20	35	35
DIMENSION A (mm)	710	710	710	680
DIMENSION B (mm)	830	1010	1110	1275
DIMENSION C (mm)	440	440	440	440
POIDS DE LA SELLE BASCULANTE (Kg)	27	27	27	27
POIDS DE L'ACCESSOIRE DE L'EXCAVATRICE (min-max Kg)	10-15	10-15	10-15	10-15

